

OVWP WALL SCNCE

- The OVWP LED wall sconce is an attractive and energy efficient solution with added benefits of LED energy savings and dusk-to-dawn controls
- Design provides a depth less than 2-1/2", making it ADA compliant
- Built-in photocell for dusk to dawn operation
- ETL Listed to US and Canadian safety standards for wet locations
- Wall mount applications more than 4' above the ground
- Rugged cast-aluminum, corrosion-resistant rear mounting plate
- Impact resistant polycarbonate front cover/diffuser resists fading and cracking
- Replaces up to 100 W incandescent lamps
- Voltage: 120 V • Wattage: 14 W
- Overall Dim.: 2.38" W x 5.31" D x 8.88" H
- Lumens: 1200
- CRI: 70
- Colour Temperature: 4000 K
- Manufacturer's Warranty: 1 Year Limited



Model No.	Mfg. No.	Colour	Price /Each
XI402	251N4X	Dark Bronze	
XI403	237Y30	White	

TWS WALL PACK LIGHT FIXTURE

- Ideal for entrances, stairwells, corridors and other pedestrian areas
- Gasketing between the backplate and front cover prevent the entry of water and contaminants
- Fixture is tamper resistant and heavy-duty, an ideal choice for your security lighting needs
- Replaces up to 100W metal halide lamps
- UL Listed to US and Canadian safety standards for wet locations
- Built-in photocell for dusk to dawn operation
- Bulb Type: LED
- Voltage: 120 - 277 V
- Wattage: 25 W
- Overall Dim.: 6.75" W x 5.25" D x 11" H
- Lumens: 2124
- CRI: 70
- Colour Temperature: 5000 K
- Manufacturer's Warranty: 5 Year Limited



Model No.	Mfg. No.	Colour	Price /Each
XI423	249NF2	Dark Bronze	

STELLA RUNNING MAN EXIT SIGNS

- Feature 120/347 VAC dual input (hardwire), universal DC; 6-24 VDC or self-powered
- Running Man sign uses a 2 watt LED source
- Long life LED light source
- Universal pictograms included showing left indicators, right indicators and no indicators
- 20-gauge steel construction with white baked powder coat paint finish
- Pre-stamped universal mounting and keyhole slots on backplate

XE662



Model No. XE662
Mfg. No. SL-RM-SP-L-U-0LR-M (Self-powered)
Price/Each \$

Model No. XE663
Mfg. No. SL-RM-L-U-0LR-M-UDC (6-24 VDC)
Price/Each \$



STELLA RUNNING MAN COMBO EXIT SIGNS

- Running Man models are supplied with 120/347 VAC dual input (hardwire)
- Push button test switch
- Self-powered for minimum 30 minutes - 6V DC 36W
- Solid state transfer charger
- Dual diagnostic LEDs indicate AC-ON and CHARGE
- Brownout and low voltage protection
- Two top mounted high impact thermoplastic PAR18 5-Watt tungsten heads
- Universal pictograms included showing left indicators, right indicators and no indicators
- 20-gauge steel construction with white baked powder coat paint finish
- Certified for sale in Canada by an accredited certification body



Model No. XE664
Mfg. No. SL-RM-6-36-L-U-0LR-M-2SR/9W
Price/Each \$



STELLA EXIT SIGNS

- C860 approved
- Standard 120/347VAC input (hardwire) and sealed nickel-cadmium batteries provide a minimum of 30 minutes of emergency duration
- Uses 2 W LED board
- Long life LED light source
- Knockout chevrons
- 20-gauge steel construction with baked powder coat white paint finish
- Pre-stamped universal mounting and keyhole slots on backplate

XB930



XB933



Model No.	Mfg. No.	Description	Dimensions W" x D" x H"	Price /Each
XB930	SLE-SP-L-R-U-M	Exit	12 x 2.25 x 7.5	
XB933	SLS-L-R-U-M-UDC	Sortie	18.5 x 2.25 x 7.5	

STELLA COMBINATION SIGNS

- C860 approved
- LED EXIT and SORTIE models 120/277/347 VAC dual input (hard wire)
- Push button test switch
- Self-powered for minimum 30 minutes -6 VDC 36 W
- Solid state transfer charger
- Dual diagnostic LEDs indicate AC-ON and CHARGE
- Brownout and low voltage protection
- Two top mounted high impact thermoplastic PAR18 9 W tungsten heads
- Knockout chevrons
- 20-gauge steel construction with baked powder coat white paint finish



Model No.	Mfg. No.	Description	Price /Each
XB929	SLE-6-36-L-R-U-M-2SR/9W	Exit	
XB932	SLS-6-36-L-R-U-M-2SR/9W	Sortie	
REPLACEMENT BULB			
XB338	LP104	9 W Tungsten	