

MOISTURE METERS

MOISTURE METERS

- Ideal for use on any construction site
- Measures the moisture content of sawn timber (also cardboard and paper) and hardened materials like plaster, concrete and mortar
- Measuring Range: Wood: 6 to 44%; Material: 0.2 to 2.0%
- Accuracy: Wood: $\pm 1\%$; Material: $\pm 0.05\%$
- Average adjustment for European wood based on a wood temperature of 20°C
- Impact-proof plastic housing
- Auto power-off
- 8 mm long integrated electrode is replaceable



REED

| Model No. | Mfg. No. | Description | Price/Each |
|-----------|----------|----------------|------------|
| IA533 | R6013 | Moisture Meter | |

MOISTURE DETECTORS

- Detects moisture content in building materials of all kinds, as well as detects moisture distribution in walls, ceilings and floors
- Non-destructive - moisture sensor runs smoothly over the surface being tested without scratching or penetrating the surface
- Display Hold button
- Max/Min function with alarm indication
- LCD display with backlighting
- Low battery indication with auto power off
- Measuring Range: 0.0 to 100.0% Moisture Content
- Penetration Depth: 20 to 40 mm



REED

| Model No. | Mfg. No. | Description | Price/Each |
|-----------|----------|-------------------|------------|
| IA681 | R6010 | Moisture Detector | |

WATER DAMAGE & RESTORATION KIT

- Pin and Pinless functions detect moisture in wood and building materials (sheet rock, cardboard, plaster, concrete and mortar)
- Displays icons to indicate low, medium or high levels of moisture and an audible alert that increases in frequency as detected moisture level rises
- Pinless measurement depth up to 1" (25mm)
- Built-in measurement verification and battery check
- Low battery indicator and auto shut-off
- Replaceable pins
- Pin Mode Measuring Ranges: 5-50% (wood); 1.5-33% (building materials)
- Pinless Mode Measuring Ranges: 0 to 99.9% (wood and building materials)
- Pin Mode Depth Detection: 0.3" (8mm)
- Pinless Mode Depth Detection: Up to 1" (25mm)
- Pin Mode Accuracy: $\pm(3\% + 5 \text{ dgt.})$
- Power Supply: 9V battery
- Display: LCD
- Operating Humidity Range: 0 to 80%
- Includes: Dual moisture meter, digital psychrometer and soft carrying case



REED

| Model No. | Mfg. No. | Description | Price/Each |
|-----------|-----------|--------------------------------|------------|
| IB874 | R6018-KIT | Water Damage & Restoration Kit | |

DUAL MOISTURE METER

- Pin and pinless functions detect moisture in wood and building materials
- Displays icons to indicate low, medium or high levels of moisture and an audible alert that increases in frequency as detected moisture level rises
- Pinless measurement depth up to 1" (25mm)
- Built-in measurement verification and battery check
- Low battery indicator and auto shut-off
- Replaceable pins
- Pin Mode Measuring Ranges: 5-50% (wood); 1.5-33% (building materials)
- Pinless Mode Measuring Ranges: 0 to 99.9% (wood and building materials)
- Pin Mode Depth Detection: 0.3" (8mm)
- Pinless Mode Depth Detection: Up to 1" (25mm)
- Pin Mode Accuracy: $\pm(3\% + 5 \text{ dgt.})$
- Power Supply: 9V battery
- Display: LCD
- Temperature Range: 41°- 113° F (5° - 45° C)
- Moisture Range: 0 - 80%
- Includes: Dual moisture meter, pins, protective caps and battery



REED

| Model No. | Mfg. No. | Description | Price/Each |
|-----------|----------|---------------------|------------|
| IB873 | R6018 | Dual Moisture Meter | |

WOOD MOISTURE METERS

- Memory contains eight wood groups with calibrations for approximately 170 species of wood
- Built-in 2-point calibration check
- User settable auto power off with override
- Low battery indication
- Integral contact pins are replaceable, remote moisture electrode pins are not replaceable
- Complete with remote hand-press moisture electrode, temperature probe, protective cap, replacement pins, two AAA batteries, and soft carrying case



SPECIFICATIONS:

Measuring Principle: Electrical resistance

Measuring Range: 6 to 99.9% MC

Accuracy: $\pm 1\%$ MC

Temp. Compensation: -31 to 176°F (-35 to 80°C)

Power Supply: Two AAA batteries

Dimensions: 7 x 1.9 x 2" (180 x 50 x 31 mm)

Weight: 6.1 oz (175 g)

REED

| Model No. | Mfg. No. | Description | Price/Each |
|-----------|----------|---------------------|------------|
| IA734 | R6015 | Wood Moisture Meter | |

COATING THICKNESS CALIBRATION KIT

- For use with coating thickness gauges



REED

| Model No. | Mfg. No. | Price/Each |
|-----------|----------|------------|
| IB875 | R9050 | |