

MR311 DRY FILM RELEASE AGENT

- Non-silicone mould release
- Exceptional anti-stick properties that will not transfer to finished parts allowing for multiple releases per application
- Compatible with most mouldable resins, elastomeric compounds, urethanes and styrenes
- Will not attack rubber, paints or metals
- Recommended for low and high-temperature moulds up to 575°F
- For polystyrenes, polypropylenes, nylon, rubber, foams, metals, filament windings, polyurethanes, epoxy potting and encapsulating and phenolic resins
- NSF Certified



Model No.	Mfg. No.	Size	Price /Each
AA174	SC0311000	12 oz.	

SF 7900™ CERAMIC SHIELD FOR WELDING

- Ceramic dry film protective coating for MIG/MAG welding processes
- Protects contact tips and welding nozzles by preventing adhesion of welding spatter
- Once applied the coating dries by solvent evaporation within 5 to 10 seconds at room temperature (Thicker films will need longer drying time)
- Ceramic, silicone-free protective coating, easy to apply
- Protects contact tips, welding nozzles and jigs, eliminating cost for cleaning equipment
- Reduces running costs for consumables by up to 40%
- Prevents adhesion of welding spatter for many hours with just one application
- Colour: White



LOCTITE

Model No.	Mfg. No.	Size	Price /Each
AD492	1616692	9.5 oz.	

SF7607™ RUBBERIZED UNDERCOATING

- Heavy-duty undercoating seals, protects, and insulates
- Rubberized for maximum durability



LOCTITE

Model No.	Mfg. No.	Size	Price /Each
AA635	234926	16 oz.	

COLOR GUARD® TOUGH RUBBER COATING

- Inhibits rust and corrosion
- Seals, insulates, and identifies almost any material in minutes
- Creates a non-slip gripping surface
- Rubber coating won't crack or chip
- Acid and alkali resistant
- Lasts for years
- Use to 200°F
- For dip, spray, or brush
- For tools, metal, electrical connections, masonry, wood, conveyors, glass, rope, fabric
- Toluene-free



LOCTITE

Model No.	Mfg. No.	Size	Colour	Price /Each
AC013	338124	14.5 oz.	Black	
AC014	338125	1 gal.	Black	
AC016	338127	14.5 oz.	Blue	
AC017	338128	1 gal.	Blue	
AC011	338130	14.5 oz.	Red	
AC012	338131	1 gal.	Red	
AC015	338134	1 gal.	Yellow	

PC 4400 PAINT PROTECT & RESTORE COATING

- Reduces repaint cycles and surface maintenance with industry leading scratch, UV, abrasion, salt and chemical resistance to extend paint life by up to 10 years
- When applied to faded or oxidized paint, PC 4400 makes the old paint look like-new again
- With both hydrophobic and oleophobic properties, PC 4400 repels water, dirt, oil and algae keeping the vehicle clean with quicker wash cycles
- Use LOCTITE 4401 as a matting additive and LOCTITE 4402 as an accelerator additive
- Key applications: Agricultural Equipment, Construction, Mining, Utility Vehicles, Salt/Plow Trucks, Specialty Buses, Rail, Military, Forestry, Freight/Delivery Trucks, Garbage Haulers, Specialty Fleet Vehicles
- Colour: Clear



LOCTITE

Model No.	Mfg. No.	Size	Price /Each
AH174	2573885	1.1 L	
AH175	2573975	3.8 L	

7332 NORDBAK® WEAR PREVENTION COATING

- Silicon carbide filled system
- Extremely high fine particle wet abrasion resistance
- Good dry and wet temperature resistance
- Easy to mix and apply; trowelable and non-sagging
- Coverage: 0.74 m² @ 6 mm thick for a 10 kg kit
- Functional cure in 6 hours
- Type: Two-Part
- Colour: Grey



LOCTITE

Model No.	Mfg. No.	Size	Price /Each
AH172	2751067	10 kg	

9593 NORDBAK® WEAR PREVENTION COATING

- Outstanding resistance to impact and wear
- Functional cure in 4 hours
- Rubber toughened polymer matrix with alumina bead and silicon carbide
- Easy to mix
- Coverage: 0.245 m² @ 6 mm thick for a 3 kg kit
- Type: Two-Part
- Colour: Clear



LOCTITE

Model No.	Mfg. No.	Size	Price /Each
AH173	2755354	10 kg	

TUMBLER PAINTABLE RUBBERIZED UNDERCOATING

- Fast drying paintable rubberized undercoating is exceptionally resistant to abrasions
- Remains flexible
- Compatible with standard automotive paints



kleen-flo

Model No.	Mfg. No.	Size	Price /Each
KR768	2785	550 g	